

SunSet™ xDSL

Aug 1997

What kind of line protection?
CE approvals - directives
Need a product definitions labels, screens,
TDR implementation, ADSL
presentation
we need to plan our equipment
development req's w/ Alcatel

SUNRISE TELECOM
INCORPORATED

PRELIMINARY SPECIFICATIONS

CONNECTORS

ADSL interface: RJ45 and Bantam.

POTS interface: RJ11 handset.

Serial-Port - 8-pin-Mini-DIN RS232C (V.24), DFE.

DC power jack.

DIGITAL DMM

DCV

0 - 350V full-scale measurement

0 - 4V range, +/- 15 mV

0 - 40V range, +/- 150 mV

0 - 350V range, +/- 1.5V

ACV

0 - 275 VAC full-scale measurement

From 50 - 500 Hz

0 - 4V range, +/- 25 mV

0 - 40V range, +/- 250 mV

0 - 275V range, +/- 2.5V

From 500 Hz - 1 kHz

0 - 4V range, +/- 87 mV

0 - 40V range, +/- 870 mV

0 - 275V range, +/- 8.7V

DCA

0 - 400 mA full-scale measurement

0 - 40 mA range, +/- 230 uA

0 - 400 mA range, +/- 2.3 mA

ACA

0 - 400 mA full-scale measurement

From 50 - 500 Hz

0 - 40 mA range, +/- 430 uA

0 - 400 mA range, +/- 4.3 mA

Resistance

0.1 ohm - 10 Mohm full-scale measurement

0.1 - 400 ohm range, +/- 4.7 ohm

0.1 - 4 kohm range, +/- 27 ohm

0.1 - 40 kohm range, +/- 270 ohm

0.1 - 400 kohm range, +/- 4 kohm

0.1 - 4 Mohm range, +/- 150 kohm

0.1 - 10 Mohm range, +/- 800 kohm

Capacitance

10 pF - 40 uF full-scale measurement

10 pF - 4 nF range, +/- 85 pF

10 pF - 40 nF range, +/- 850 pF

10 pF - 0.4 uF range, +/- 8.5 nF

10 pF - 4 uF range, +/- 85 nF

10 pF - 40 uF range, +/- 850 nF

DIGITAL TMS

Wideband TMS: 10 kHz to 1.5 MHz

Resolution: 375 Hz

Level

Tx: -30 to 16 dBm

Rx: -60 to 14 dBm

Flatness: 0.1 dB

Output Impedance: 100 ohm

Signal to Noise (S/N) measurement

Please
provide me with feedback
by our 9/22/97 meeting.
George

TDR

Range*

10 - 22,000 ft for 22 AWG

10 - 18,000 ft for 24 AWG

10 - 12,000 ft for 26 AWG

Pulse

1/2 square wave

Amplitude

5 Vpp into 100 ohm

10 Vpp into open circuit

Width

20 ns - 5 us

Adjustable velocity: 0.4 to 0.99

Output Impedance: 100 ohm

Accuracy

10 - 1000 ft, +/- 4 ft

1000 - 22,000 ft, +/- 6 ft

Display results to LCD screen.

Store 3 previous test results in graphical format.

* Dependent upon condition of wire and the number of bridge taps

ALCATEL ADSL PLUG-IN MODULE

Alcatel 3.0 chip set implementation.

Establish ADSL link with far end modem.

Up/down stream bit rate verification and BERT test.

IEEE 743 F & G filter noise measurement

Signal to Noise (S/N) measurement

Other modules to be announced.

RCP
PM
K.C.C
TD
RK
VW
CLW
MM
SG
RC
IP

SunSet™ xDSL

SUNRISE TEL
INCORPORATED

POTS SPLITTER EMULATION

Emulate POTS splitter applications.
Provide direct handset interface/built-in hook control.
POTS shunt circuit on/off control.

no longer in there

GENERAL

Size: 10.5 x 6 x 27 cm (4 x 2.4 x 10.5")

Weight: 1.3 Kg (2.8 lb)

Construction: PC+ABS high-impact plastic.

Display: 32x16 graphic LCD with backlight.
18 bi-color LEDs.

Battery: Rechargeable, field-replaceable NiMH pack.
Provides 5 hrs of continuous use (nominal).

Charger: Universal design with IEC power cable connector.
11 x 6 x 3.5 cm (4.3 x 2.4 x 1.4") with 122 cm (4')
extension cable attached.

9.75 oz.

100 VAC - 240 VAC input.

15 VDC, 2A output.

Fast recharge in 3 hours (nominal).

UL, CSA, CE approved.

Upgrade options via field-replaceable SunWare™ cartridge.

ENVIRONMENTAL

Operating temperature: 0 to 50 °C (32 to 122 °F)

Storage temperature: -20 to 70 °C (-4 to 158 °F)

Humidity: 5% to 90% noncondensing

Note: Specifications subject to change without notice.